


UNI 6752

- Profilo interno a raggi multipli per una perfetta aderenza di ghiera unificate e per cuscinetti.



art.	art.	Ø mm	S mm	B mm	L mm	A mm	g
000990012	99 12-14	12-14	3,0	14,5	109	1,5	21
000990016	99 16-20	16-18-20	3,0	14,5	109	1,8	21
000990022	99 22-28	22-25-28	4,0	21,0	136	1,8	43
000990030	99 30-32	30-32	4,0	21,0	136	2,1	39
000990034	99 34-38	34-36-38	5,0	28,5	171	2,4	83
000990040	99 40-42	40-42	5,0	28,5	171	2,4	78
000990045	99 45-50	45-50	6,0	37,0	206	2,5	146
000990052	99 52-58	52-55-58	6,0	37,0	206	2,5	137
000990062	99 62-65	62-65	7,0	46,0	242	3,1	226
000990068	99 68-75	68-70-75	7,0	46,0	242	3,1	228
000990080	99 80-90	80-85-90	8,0	62,0	281	3,8	368
000990092	99 92-95	92-95	8,0	62,0	283	4,3	360
000990098	99 98-100	98-100	8,0	62,0	283	4,3	357
000990105	99	105-110-115	10,0	81,0	337	4,4	668
000990120	99	120-125-130	10,0	81,0	337	4,9	672
000990135	99 135-145	135-145	12,0	98,0	385	6,0	1100
000990155	99 155-165	155-165	12,0	98,0	385	6,0	1120